

INSULATION RESISTANCE METER MIC-10k1 / MIC-5050

**INSULATION
RESISTANCE
MEASUREMENT UP TO
40 TΩ
IN ACCORDANCE
WITH IEC 61557-2
MIC-10k1**



CAT III
1000V

CAT IV
600V

EN
61557-2

 **Bluetooth®**

WIRELESS DATA TRANSMISSION

Insulation resistance measurement:

- up to 40 TΩ for MIC-10k,
- up to 20 TΩ for MIC-5050,
- measurement voltage any in the range of:
 - 50...5000 V for MIC-5050 (50...1000 V at 10 V and 1...5 kV at 25 V),
 - 50...10000 V for MIC-10k1 (50...1000 V at 10 V and 1...10 kV at 25 V),
- continuous indication of measured insulation resistance or leakage current,
- automatic discharge of measured object capacitance voltage after the end of insulation resistance measurement,
- acoustic signaling of 5 seconds intervals to facilitate capturing time characteristics,
- adjustable measuring time to 99'59",
- metered T_1 , T_2 and T_3 test times for measuring one or two absorption coefficients from the range of 1...600 s,
- polarization index (PI), absorption coefficients Ab1, Ab2 and dielectric absorption ratio (DAR) measurement,
- indication of actual test voltage during measurement,
- 1.2 mA, 3 mA and 5 mA test current,
- insulation resistance measurement using two- or three-wire method,
- measurements with test leads up to 20 m...
- protection against measuring live objects,
- automatic measurement of multiple core cables with the additional AutoISO-5000 adapter (for MIC-10k1 max. voltage 5 kV)
- measurement of capacitance during the measurement of R_{ISO} ,
- measurement of temperature (with additional probe - WASONT1),
- step voltage insulation resistance measurement (SV),
- Dielectric Discharge calculation (DD),
- location of damage (burnout),
- digital filters function for measurements in high noise environment,
- continuity measurement of protective connections and equipotential bonding in accordance with EN 61557-4 with current ≥ 200 mA,
- adjustable limits for measured resistance R_{ISO} ,
- measurement of leakage current during insulation resistance testing,
- DC and AC voltage measurement in the range of 0...750 V,
- drawing graphs on the display during measurement,
- innovative memory with possibility of description of: measurement points, facilities, names of customers.
- operating with mini Bluetooth keyboard (option),
- graphic LCD 5,6" backlit,
- keyboard backlit,
- power supply from main power line or battery packs,
- built-in fast charger,
- the instruments meet the requirements of the EN 61557 standard.

NEW!

Sonel S.A.
Wokulskiego 11
58-100 Świdnica, PL
tel. +48 74 85 83 860
fax +48 74 85 83 809

export@sonel.pl
www.sonel.pl

MIC-10k1 / MIC-5050

Insulation resistance measurement

Measurement range acc. to IEC 61557-2 for MIC-5050 $U_{iso} = 5000V: 5,00M\Omega \dots 20,0T\Omega$, for MIC-10k1 $U_{iso} = 10000V: 10,0M\Omega \dots 40,0T\Omega$

Range	Resolution	Accuracy
0...999 k Ω	1 k Ω	$\pm(3\% \text{ m.v.} + 10 \text{ digits})$
1,00...9,99 M Ω	0,01 M Ω	
10,0...99,9 M Ω	0,1 M Ω	
100...999 M Ω	1 M Ω	
1,00...9,99 G Ω	0,01 G Ω	
10,0...99,9 G Ω	0,1 G Ω	$\pm(3,5\% \text{ m.v.} + 10 \text{ digits})$
100...999 G Ω	1 G Ω	
1,00...9,99 T Ω	0,01 T Ω	$\pm(7,5\% \text{ m.v.} + 10 \text{ digits})$
10,0...20,0 T Ω	0,1 T Ω	$\pm(12,5\% \text{ m.v.} + 10 \text{ digits})$
10,0...40,0 T Ω^*		

* - only for MIC-10k1, $U_{iso} = 10 \text{ kV}$

Values of measured resistance depending on measurement voltage

Voltage U_{iso}	Measurement range	AutoISO-5000 measurement range
50 V	200 G Ω	20,0 G Ω
100 V	400 G Ω	40,0 G Ω
250 V	1,00 T Ω	100 G Ω
500 V	2,00 T Ω	200 G Ω
1000 V	4,00 T Ω	400 G Ω
2500 V	10,00 T Ω	400 G Ω
5000 V	20,0 T Ω	400 G Ω
10 000 V*	40,0 T Ω^*	-

* - only for MIC-10k1

Step voltage insulation resistance measurement

Voltage U_{iso}	MIC-5050	MIC-10k1
50...1000 V	10 V	10 V
1000...5000 V	25 V	25 V
5000...10000 V	-	25 V

Continuity measurement of protective connections and equipotential bonding with 200 mA current

Measurement range acc. to EN 61557-4: 0,12...999 Ω

Range	Resolution	Accuracy
0,00...19,99 Ω	0,01 Ω	$\pm(2\% \text{ m.v.} + 3 \text{ digits})$
20,0...199,9 Ω	0,1 Ω	
200...999 Ω	1 Ω	$\pm(4\% \text{ m.v.} + 3 \text{ digits})$

- Voltage on open terminals: 4...24 V
- Output current at $R < 15 \Omega$: min. 200 mA (I_{sc} : 200...250 mA)
- Compensation of test lead resistance
- Current flowing in both directions, mean value of resistance is displayed

DC and AC voltage measurement

Range	Resolution	Accuracy
0,0...29,9 V	0,1 V	$\pm(2\% \text{ m.v.} + 20 \text{ digits})$
30,0...299,9 V	0,1 V	$\pm(2\% \text{ m.v.} + 6 \text{ digits})$
300...750 V	1 V	$\pm(2\% \text{ m.v.} + 2 \text{ digits})$

- Frequency range 45...65Hz

Measurement of capacitance

Display range	Resolution	Accuracy
0...999 nF	1 nF	$\pm(5\% \text{ m.v.} + 5 \text{ digits})$
1,00...49,99 μF	0,01 μF	

- capacity measurement result is displayed after the R_{iso} measurement
- for measuring voltages under 100 V capacitance measurement accuracy not specified.

Measurement of temperature

Display range	Resolution	Accuracy
-40,0...99,9 °C	1 °C	$\pm(3\% \text{ m.v.} + 8 \text{ digits})$
-40,0...211,8 °F	1 °F	$\pm(3\% \text{ m.v.} + 16 \text{ digits})$

Standard accessories:

- test lead banana plug; 3 m; 10kV; red
- test lead „E“ banana plug; 3 m; 10 kV; blue
- test lead banana plug; 3 m; 10kV; black; shielded
- USB cable
- "crocodile" clip 11 kV; black
- "crocodile" clip 11 kV; red
- "crocodile" clip 11 kV; blue
- pin probe 11 kV with banana connector; red
- pin probe 11 kV with banana connector; black
- carrying case L4 for accessories
- power cord
- temperature probe ST-1
- battery pack (built-in)
- "SONEL Reader" software
- calibration certificate

WAPRZ003REBB10K
WAPRZ003BUBB10K
WAPRZ003BLBBE10K
WAPRZUSB
WAKROBL32K09
WAKRORE32K09
WAKROBU32K09
WASONREGB11
WASONBLOGB11
WAFUTL4
WAPRZ1X8BLIEC
WASONT1

Electrical safety:

- type of insulation double, EN 61010-1 and IEC 61557 compliant
- measurement category IV 600 V (III 1000 V) according to EN 61010-1
- degree of housing protection acc. to EN 60529 IP40 (IP67 for closed enclosure)

Other technical specifications:

- power supply of the meter 12 V Li-Ion battery
90 V \div 260 V 50 Hz/60 Hz from the electric grid
- dimensions 390 mm x 310 mm x 180 mm
- meter weight approx. 5,6 kg
- storage temperature -25°C...+70°C
- working temperature -20°C...+50°C
- humidity 20%...90%
- altitude (above sea level) \leq 3000 m
- reference temperature +23 °C \pm 2 °C
- reference humidity 40%...60%
- display LCD 5,6", segment-type
- transmission of measurement results USB or Bluetooth
- number of R_{iso} measurements, acc. to EN 61557-2 with battery power supply min. 1000
- quality standard design, construction and manufacturing are ISO 9001, ISO 14001, PN-N-18001 compliant
- the device meets the requirements of the EN 61010-1 and IEC 61557 standards
- the product meets EMC requirements (immunity for industrial environment) according to the following standards EN 61326-1:2006 and EN 61326-2-2:2006

The acronym "m.v." stands for a "measured reference value".